

JMLU2.MH62756 - Gaskets and Seals - Component

Gaskets and Seals - Component

Dongguan Guangmai Electronic Technology Co Ltd

16B Building International Finance IT Research and Development Center No 5 Keji Ten Road
Songshan Lake High-Tech Industrial Development Zone
Dongguan, Guangdong 523808 China


MH62756

Cellular Material

Compound Dsg.	Max Svc Temp (°C)	Min Svc Temp (°C)	Density (pcf)	Tensile Str (psi)	Elong (%)	Max Comp Set (%)
---------------	-------------------	-------------------	---------------	-------------------	-----------	------------------

Silicone						
GM-400	135	-40	28.1	42.3	88	1.28
	End Use: 1, 2 Suitable for UL 50E continuous and periodic compression applications for enclosures Types 2, 3, 3X, 3R, 3RX, 3S, 3SX, 4, 4X, 5, 6, 6P, 12, 12K and 13 including oil immersion					

The final acceptance of a gasket material in a specific end-use application is dependent on its installation and use, and may require additional evaluation with respect to ingress or leakage of solids (such as dusts), liquids or gases, or other features dependent on the design and construction of the equipment in which it is used.

Marking: Company name, compound designation and the Recognized Component Mark,  On the material, On a substantial tag, On the container Or the smallest packaging.

Last Updated on 2022-08-22

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."